





Performance:

- Articulated pendulum joint ensures maximum traction and maneuverability, on any terrain
- Compact design and maximum productivity with high payload capacity
- Universal attachment plate makes these machines ideal tool carriers for a variety of jobs

Efficiency/comfort

- Hydraulic quick coupler allows operator to easily switch attachments from the driver's seat
- Comfortable operation with ergonomic, single joystick control and spacious operating platform
- Large windows provide excellent view and enhance job site safety



Maintenance

- Excellent service access with wide doors
- Lubrication points are easily accessible, saving time

Performance Data

Unit	WL250	WL28	WL34	WL38	WL52	WL60	WL95
Max. operating power at operating speed	hp rpm	25 @ 2,800	44.7 / 53.8 @ 2,600	60.3 @ 2,300	74.3 @ 2,300	74.3 @ 2,300	101 @ 2,200
Engine type		Perkins 403J-17, water-cooled, 3-cylinder, diesel engine	Yanmar 3TNV86CHT, Yanmar 3TNV86CHT-HP liquid cooled, 3 cylinder, turbo diesel engine.	Deutz TD 2.9 L4 S5, liquid cooled, 4 cylinder, turbo diesel engine.	Deutz TCD 2.9 L4, liquid cooled, 4 cylinder, turbo diesel engine.	Deutz TCD 2.9 L4, liquid-cooled, 4-cylinder, turbo diesel engine.	Perkins 904J-E36TA, liquid-cooled, 4-cylinder, turbo diesel engine.
Tipping load (bucket / fork) - straight - articulated	lbs	3,616 / 2,690 3,064 / 2,271	4,145 / 3,439 3,395 / 2,866	3,638 / 3,417 3,109 / 2,932	6,449 / 5,765 5,386 / 4,850	8,199 / 6,989 6,863 / 5,869	8,706 / 6,735 7,531 / 5,633
Rated Operating Capacity (bucket) - straight (50%) - articulated (50%)	lbs	1,808 1,532	2,073 1,698	1,819 1,555	3,225 2,693	4,100 3,432	4,050 3,341
Rated operating capacity (fork) - fully articulated hard surface (80%) - fully articulated rough terrain (60%)	lbs	1,817 1,532	2,293 1,720	2,337 1,764	3,880 2,910	4,695 3,521	4,922 3,692
Bucket capacity	yd³	0.27	0.5	0.75	0.75	1.1	1.3
Fuel tank capacity	gal	4.8	13.2	17.2	17.2	21.7	27.7
Hydraulic tank capacity	gal	4.8	7.9	13.2	13.2	17.4	25.1
Travel speed	mph	0 - 12.43	0 - 12.4 / 0 - 18.6	0 - 12.4	0 - 18.6	0 - 12.4 / 0 - 18.6	0 - 24.9
Aux. hydraulic flow rate standard high flow	gpm	11.8	13.1 22.2	15.2 -	15.1 30.6	19.4 30.4	26.4 39.6
Pressure	psi	2,683	3,046	3,046	3,046	3,046	3,626
Overall length with bucket	in	150.8	178.0 / 182.3	203.1	203.1	213.5	232.3
Overall width	in	38.6	44.4 / 54.9	61.0	61.8	71.3	72.0
Overall height*	in	78.3	91.8 / 92.5	93.3 / 94.8	100.4	105.3	107.1
Hinge pin height	in	98.8	100.1 / 126.4	128.7	128.0	127.4	145.3
Operating weight with cab	lbs	4,630	7,275	8,598	9,480	11,244	13,007
Standard tires		315/55 R16 Continental MPT81 ET-30	31x15.5-15 ET-37	15.5/55-18 EM ETO	15.5/55-18 EM ETO	405/70 R18 EM ETO	405/70-18 EM ETO
							500/70 R24 ET40



www.wackerneuson.com

©Wacker Neuson 2025. Right to make technical amendments reserved.



0986256
2 / 2025