



**WACKER  
NEUSON**  
*all it takes!*

# Dumpers

## Wheeled and Dual View



### Material movers

Articulated wheeled dumpers are excellent for moving bulk materials. The smaller foot print allows dumpers to maneuver around confined and busy job sites, moving materials faster and significantly improving cycle times.



### Always facing the task

With our Dual View dumpers, the operator can quickly and comfortably change the seat and console position to keep the task front and center. The entire operating platform rotates 180 degrees, giving the best view while working or driving the machine.

## Performance Data

	Unit	DW30	DW30 Concrete edition	DW50
<b>Max. operating power at operating speed</b>	<b>hp rpm</b>	45.3 @ 2,200	45.3 @ 2,200	59.7 @ 2,300
<b>Engine type</b>		Perkins 403J-E17T, liquid-cooled, 3-cylinder turbo diesel engine.	Deutz TD 2.2, liquid-cooled, 3-cylinder turbo diesel engine.	
<b>Fuel tank capacity</b>	<b>gal</b>	11.9	11.9	15.9
<b>Travel speed</b>	<b>mph</b>	0-15.5	0-15.5	0-15.5
<b>Standard tires</b>		11.50/80 x 15.3, Mitas tractor tread	12.5-18/16, Mitas universal tread	
<b>Final drive</b>		Hydrostatic transmission, permanent 4-wheel drive, electronic driving direction switch.		
<b>Working brake</b>		Hydrostatic / Wet multidisk		
<b>Pump capacity Operating / Drive</b>	<b>gal/min</b>	8.2 / 26.2	8.2 / 26.2	14 / 32.5
<b>Operating pressure Operating / Drive</b>	<b>psi</b>	2,901 / 6,498	2,901 / 6,498	3,191 / 7,252
<b>Hydraulic tank capacity</b>	<b>gal</b>	11.1	11.1	10.6
<b>Height ROPS/CAB</b>	<b>in</b>	112.6 / 105.1	112.6 / –	110.8 / –
<b>Width</b>	<b>in</b>	70.1	70.1	75.8
<b>Length</b>	<b>in</b>	166.3	199.3	177.0
<b>Max safe payload</b>	<b>lb</b>	6,614	6,614	11,023
<b>Skip capacity leveled heaped water</b>	<b>yd<sup>3</sup> yd<sup>3</sup> gal</b>	1.67 2.29 262		2.62 3.47 3.49
<b>Transport weight ROPS / CAB</b>	<b>lbs</b>	5,545 / 5,895	5,675 / –	7,580 / –

## Dual View Dumpers

	Unit	DV60	DV90	DV100	DV125
<b>Max. operating power at operating speed</b>	<b>hp rpm</b>	74.2 @ 2,200	74.2 @ 2,200	74.2 @ 2,200	135.9 @ 2,200
<b>Engine type</b>			Deutz TD2.9 L4, liquid-cooled, 4-cylinder, diesel engine.		Deutz TDC3.6 L4, water-cooled, 4-cylinder, turbo diesel engine.
<b>Fuel tank capacity</b>	<b>gal</b>	21.1	21.1	21.1	39.4
<b>Travel speed</b>	<b>mph</b>	0-18.6	0-18.6	0-18.6	0-15.5
<b>Standard tires</b>		405/70-20 (Mitas, MPT-01)	500/60-22.5 (Alliance, Flotation 331)	600/50-22.5 (Alliance, flotation 331)	
<b>Turning radius outside</b>	<b>in</b>	240.6	260.6	259.8	283.0
<b>Final drive</b>		Hydrostatic transmission, permanent 4-wheel drive, electronic driving direction switch.			
<b>Working brake</b>		Hydrostatic / Wet multidisk			
<b>Pump capacity Operating / Drive</b>	<b>psi</b>	19.4 / 32.6	19.4 / 32.6	19.4 / 32.6	18.0 / 39.0
<b>Operating pressure Operating / Drive</b>	<b>gal</b>	3,481 / 7,252	3,481 / 7,252	3,481 / 7,252	3,480.9 / 8,702.3
<b>Hydraulic tank capacity</b>	<b>gal</b>	15.9	15.9	15.9	14.5
<b>Height ROPS/CAB</b>	<b>in</b>	135.2 / 115.2	- / 119.3	- / 119.3	- / 120.6
<b>Width</b>	<b>in</b>	87.3	96.6	98.6	99.1
<b>Max safe payload</b>	<b>lb</b>	13,228	19,841	22,046	27,557.8
<b>Skip capacity leveled heaped water</b>	<b>yd<sup>3</sup> yd<sup>3</sup> gal</b>	3.1 4.1 423	4.3 5.7 542	5.4 6.5 674	9.0 10.7 977.5
<b>Transport weight ROPS / CAB</b>	<b>lbs</b>	8,715 / 9,469	- / 10,814	- / 10,869	- / 14,056.7



[www.wackerneuson.com](http://www.wackerneuson.com)

©Wacker Neuson 2025. Right to make technical amendments reserved.

## Performance

- Hydrostatic drive offers simple, intuitive operation. The four-wheel drive provides perfect traction on difficult terrain and articulated steering allows for a tight turning radius

## Efficiency

- Heavy-duty, impact resistant swivel skip allows material to be unloaded from the front or either side, making dumping more precise and efficient

## Maintenance

- Extended maintenance intervals of 500 operating hours provides additional cost savings

